

Specifications

ENGINE	- Electronic, Common rail, Teir 4
MAKE/MODEL	- Kubota / V3307
TYPE	4, Vertical in line
HORSEPOWER	- 54,6 kW (73 HP)
AFTER TREATMENT	- DPF
CERTIFICATION	- CANMET
FUEL	- DIESEL
CAPACITY	- 80,0 L (21,13 gal)
AXLES	- 2 steering, with 4 planetary reduction gears
TRANSMISSION	- Single speed Hydrostatic transmission with variable displacement pump
STEERING	- Hydraulic Power Steering
DRIVE SYSTEM	- 4WD
BRAKES (PARK/EMERGENCY)	- Front and Rear Multi Wet Disk brakes, Axle Enclosed SAHR
BRAKES (SERVICE)	- Enclosed, Wet disc
TIRES	- 6/11-16, INDUSTRIAL 22 PLY
SOUND LEVEL (OPERATOR)	- 85 dB (A)
PAYLOAD CAPACITY	- 2600 kg (5732 lb)

GROUND CLEARANCE	270MM (10.6 in.)
REACH AND CAPACITY	- Maximum capacity 2600 kg (5732 lb) - Maximum lifting height 5,68 m (18,6 ft) - Maximum horizontal reach 3,2 m (10,5 ft) - Fork swiveling angle 129°
BOOM	- Lifting 7,8 s - Descent 4,1 s - Extension 6,1 s - Retraction 3,4 s - Forward swiveling 3,5 s - Reverse swiveling 2,2 s
ELECTRICAL	- Mine Compliant Harness - Standard Wiring Integration - Standard overhead LED Lights, Beacons - Heavy-duty switches - 12V Battery
AVAILABLE CONFIGURATIONS	- Forklift - Manbasket - Bucket - Hoisting Crane - Sweeper

MINEMASTER®

Apollo 26.6

Specifications subject to change without prior notice

TRACKS + WHEELS

tracksandwheels.com

minemaster.com

We have built the MINEMASTER® product in several standard configurations to suit a variety of applications. We also design and build custom units based on our customers' unique needs and requirements.

Contact us at sales@minemaster.com for complete specifications and general arrangement of drawings of the MINEMASTER® you require.



SUDBURY

400 Hwy. 69 N. Box 2592
Sudbury, Ontario
Canada P3A 4S9
tel 705 566 5438
fax 705 566 5422

TIMMINS

2200 Riverside Dr. RR2
Timmins, ON
Canada P4R 0A1
tel 705 268 5438
fax 705 268 3382

NORTH BAY

127 Pinewood Park Drive
North Bay, ON
Canada P1B 8Z4
tel 705 840 5438
fax 705 474 0717



Apollo Series

The Apollo 26.6 is the leader when it comes to underground telehandlers. The Apollo has a industry leading 5700lbs capacity, while maintaining in a small footprint. It comes standard with important safety features including : axle load sensors, deadman switched on controls, manbasket stability package, and more.

STRONG POINTS

- + Optional Fire Suppression (70L Hydraulic Oil)
- + Sealed Axle Brakes (No Driveline brakes)
- + CANMET certified diesel engines
- + MineMaster Harness and Lighting System
- + Heavy-duty skid plates for protection
- + Simple Design and Components
- + Dual steering axles; exceptional maneuverability and tight turning radius

Operator Compartment

STANDARD CAB Configuration

Open Cab Configuration

AC and Heat

Standard Features

Multi-WET SAHR Emergency Brakes

4-Wheel Steering

16 Ft Lift Height

Axle Weight Sensors with Overload warning

Front Attachments

- + Manbaskets
- + Forks
- + Cranes
- + Buckets
- + Request attachment Catalog for more options

